

DVR- F1108

8CH/1 SATA DVR




KEY FEATURES

- 1 SATA (Maximum support 6TB)
- Support AHD / TVI 720P/1080P
- Support VGA, HDMI 1080N HD output
- Video Compression H.264 High Profile
- 4Ch Audio Input/ 1 Ch Audio Output

DVR- F1108 8CH/1 SATA DVR

DIMENSION



INTERFACE



SPECIFICATION

VIDEO

Video Compression	H.264 High Profile
Encode Ability	8ch*1080N@15fps
Decode Ability	8ch *1080N@15fps
Video Input (Pure Analog)	Pure Analog: 8ch*720P Support 8ch*1080P
Mixed	4ch*AHD(720P)+4ch*TVI(720P) 4ch*AHD(1080P)+4ch*IPC(720P)
Support	4ch*AHD(1080P)+4ch*TVI(1080P) 4ch*AHD(1080P)+4ch*IPC(1080P)
Pure Network	8ch*720P Support 8ch*1080P

AUDIO

Audio Compression	G.711A
Two Way Audio	Support

RECORD AND PLAYBACK

Hard Drive	1 SATA (Maximum support 6TB)
Record	Manual/Event/Timer
Playback	8ch(pure local input mode)

STORAGE & BACK UP

Space Occupation	960H:12~20G/ day*channel 720P:~20G/ day*channel 1080P 20~30G/ day*channel Audio:691.2M/ day*channel
Backup Mode	USB HDD

INTERFACE

Video Input	8ch BNC (AHD/TVI/CVBS)
Video Output	1ch VGA,1ch HDMI
Audio Input	4ch RCA
Audio Output	1ch RCA
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB

GENERAL

Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L) x 255mm(W) x 45mm(H)